

Linear D.C. Power Supply



GPR-M Series



FEATURES

- * 0.01% High Regulation
- * Constant Voltage and Constant Current Operation
- * Internal Select for Continuous or Dynamic Load
- * Low Ripple and Noise
- * Overload and Reverse Polarity protection
- * 3 1/2 Digit 0.5" LED Display

SPECIFICATIONS

CONSTANT VOLTAGE OPERATION	
Regulation	Line regulation $\leq 0.01\% + 3\text{mV}$ Load regulation $\leq 0.01\% + 5\text{mV}$ ($<10\text{A}$) Load regulation $\leq 0.02\% + 5\text{mV}$ ($\geq 10\text{A}$)
Ripple & Noise	$\leq 1\text{mVrms}$ 5Hz ~ 1MHz
Recovery Time	$\leq 100\mu\text{S}$ (50% load change, minimum load 0.5A)
Output Range	0 to rating voltage continuously adjustable
CONSTANT CURRENT OPERATION	
Regulation	Line regulation $\leq 0.2\% + 3\text{mA}$ Load regulation $\leq 0.2\% + 3\text{mA}$
Ripple Current	$\leq 3\text{mA rms}$
Output Range	0 to rating current continuously adjustable
METER	
Digital	3 1/2 Digits 0.5" LED display Accuracy $\pm (0.5\% \text{ of rdg} + 2 \text{ digits})$
INSULATION	
Chassis and Terminal	$20\text{M}\Omega$ or above (DC 500V)
Chassis and AC Cord	$30\text{M}\Omega$ or above (DC 500V)
POWER SOURCE	
AC 100V/120V/220V/240V $\pm 10\%$, 50/60Hz	
DIMENSIONS	
254(W) x 152(H) x 349(D) mm	

ORDERING INFORMATION

Model	Output Volts (V)	Output Amps (A)	Weight (kg)
GPR-1810HD 180W D.C. Power Supply	0 ~ 18	0 ~ 10	11.5
GPR-3060D 180W D.C. Power Supply	0 ~ 30	0 ~ 6	11.5
GPR-6030D 180W D.C. Power Supply	0 ~ 60	0 ~ 3	11.5
ACCESSORIES : User manual x 1 , Power cord x 1 Test lead GTL-105A x 1 (GPR-6030D) GTL-104A x 1 (GPR-1810HD/3060D)			
OPTIONAL ACCESSORIES			
GRA-401 Rack Adapter Panel (19" , 4U)			